



800.253.1569 | wensco.com

## ► Series 5500 Diffuser Film

### Series 5500: Non-Perforated

#### APPLICATIONS & FEATURES

- Designed for second surface applications of internally illuminated signage and displays.
- Environmentally friendly alternative to back spraying.
- Excellent long-term adhesion.
- Uniform light control.
- 7 year outdoor durability.

#### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	25 to 40 units	
<b>TRANSMISSION VALUES</b>	Spectrophotometer	#30 - 30%	#70 - 60%
<b>THICKNESS</b>	Micrometer, Federal Bench Type	English: 0.0034 in	Metric: 0.09 mm
<b>TENSILE STRENGTH</b>	Tensile Tester 2-in (51mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s)	4.5 lb/in width	0.8 kg/cm width
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 150 %	
<b>SHELF LIFE</b>	Free from excessive moisture, temperature, direct sunlight	2 years from factory shipment	
<b>APPLICATION TEMPERATURE RANGE</b>	On clean substrate	60°F to 90°F optimum	15°C to 32°C optimum
<b>SERVICE TEMPERATURE RANGE</b>	Film applied to etched aluminum panels 24 hours prior to testing	-40°F to 200°F	-40°C to 93° C
<b>HUMIDITY RESISTANCE</b>	Film applied to etched aluminum panels 24 hours prior to testing; 100% relative humidity at 100°F (38°C) for 500 hours	No appreciable effect	
<b>DIMENSIONAL STABILITY</b>	158°F (70°C), 48 hours	0.015 in	0.4 mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min, RT 70°F (21°C)	≥ 60 oz/in	≥ 0.67 kg/cm
<b>LINER RELEASE</b>	TLMI 300 in/min (760 cm/min)	150 g/2 in	30 g/cm

\*Standard Terms & Conditions Apply

## DURABILITY

Seven (7) years. Durability will be affected by actual exposure conditions and sign face maintenance.

## USAGE AND APPLICATION INFORMATION

For best results on large, continuous-color signs, be sure to utilize material from identical rolls on the same sign face to assure consistent light diffusion so as not to adversely affect the color reflection and transmission across the sign face.





## NOTICE TO PURCHASER








Information is based on tests believed to be reliable, but neither accuracy nor completeness is guaranteed. Seller's and manufacturer's only obligation shall be to replace such quantity of the film proven to be defective. Neither the seller nor the manufacturer shall be liable for any injury, loss or damage, direct or indirect, arising from the use or inability to use this product.

## TERMS & CONDITIONS

The customer assumes responsibility in determining product suitability for his intended end use. Seller's and manufacturer's only obligation shall be to replace product proven to be defective. Standard terms and conditions apply.

April 2014

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK  
INDIA:  4F1 Court Chambers 35, New Marines Lines, Mumbai 400 020, India

 800 232 7161 / 714 540 2811  800 329 2756  
 +31 0 70 354 4311  +31 0 70 355 7721  
 +44 0 161 884 0592  +31 0 70 355 7721  
 +91 99 6755 3895

arlon.com