

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS



SUBLIBLOCK® TURBO

- Reformulated for use with modern performance polyesters
- Low temperature prevents heat-press marks on polyester garments
- Has a soft hand, excellent opacity, and blocks dye-migration
- Pressure-sensitive carrier enables easy weeding and repositioning

Acceptable Fabrics

Cotton, Uncoated Polyester, Cotton/Polyester, Polyester/Acrylic

Excluding Nylon. Test on dazzle cloth & moisture-wicking fabrics.

Sizing Available

Available Widths (in.): 15", 20", and 30"

Available Lengths (ft.): 15', 30', 45', 60', and 90' rolls

Thickness


5.2 mils/130 microns



White
SB-3105-T



Antique Silver
SB-3834-T



Old Gold
SB-3843-T



Neon Pink
SB-3910-T



Neon Yellow
SB-3920-T



Neon Orange
SB-3930-T



Neon Green
SB-3940-T



45° Blade
Recommended



Cut this material
in mirror image



270°F



Medium, even
pressure



5 Seconds



Peel Warm



Wash inside-out,
wash warm, tumble-dry
normal. Suitable
for dry-cleaning.



800.253.1569 | wensco.com

Technical Support: Toll Free: 877-437-8556 | SpecialtyMaterials.com

All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability whatsoever in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer. Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing.

Copyright © 2018, Specialty Materials & Digital Decoration, LLC. All rights reserved.