



# Gfp

**Graphic Finishing**  
partners

Where Finishing Comes First.

## Gfp 563TH-4RS

### ProductionTop Heat Laminator

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? The 563TH-4RS does all that and more.

#### MAXIMIZE PRODUCTIVITY

*Inline Rotary Slitters*

#### FAST ROLL CHANGES

*Front/Rear Swing-out shafts*

#### EASY LOADING

*3" Aluminum Quick-Grip shifts*

#### RUGGED DESIGN

*Metal Alloy heaters*

#### VERSATILE

*Roll-to-Roll operation*



***overlamination • mounting • board pre-coating***

***Spend less time on set-ups and changeovers with swing-out supply shafts.***

50% faster throughput and quick application changes save time, effort and money.



- Swing-out Quick-Grip supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for safety
- Includes rear rewind with Rotary Slitters
- Swing-up feed table & 38" output height
- Metal Alloy heater reduces breakage
- 4.4" diameter rollers
- Roller gap measurement scale



Includes motorized rear rewind with rotary slitters for roll-to-roll applications



Media Alignment disks keep supply rolls from telescoping

## 563TH-4RS

Rugged Design  
Professional Quality  
Proven Performance  
Economically Priced

### APPLICATIONS

Signs  
Banners  
POP Displays  
Trade show displays  
Graphic mounting  
Photo mounting  
Dry-erase boards  
Floor graphics  
Window graphics  
Vehicle graphics

### Warranty:

1 year parts & labor.  
Installation is available.

Laminating Width	63"
Roller Diameter	4.5"
Roller Gap	1"
Rear rewind with Slitters	Included
Maximum temperature	140°F
Laminating speed	0-20 ft/min
Pressure adjustment	Hand Wheel
Heat method	Metal Alloy heater
Max. roll diameter	8" OD (top); 16" OD (bottom)
Supply Shafts	2 Swing-out
Tension Adjustment	Single knob
Power Supply	110v 12A
Power Consumption	1320W
Foot Pedal	Included
Stand with casters	Included
Dimensions	87" x 26.5" x 52.5"
Net Weight w/ stand	491 lbs.
Shipping Dimensions (L x W x H)	89" x 35" x 52" 791 lbs.

cTUVus  
Safety  
Approval



Your local dealer is:

**wensco**  
800.253.1569 | wensco.com

