

# LED GUIDE

√ - Yes All 12 VDC unless noted

\* Multiple options V- varies per color/length

	Top Sellers	LEDs / module	Modules / ft / sqft	Lumens / module	Lumens / ft / sqft	Color Temp / Colors	IP Rating	W / Module	Modules/ft per 60 W Power Supply	Viewing Angle	Channel Letters	Cabinet Lighting	Fluorescent Replacement	Awnings/Soffits/Wall Wash	Catalog Page
G2G LED	PROPERTIES										APPLICATIONS				
Aurora I Gen 4 White LED Modules	√	3	3	65	195	7500K	68	0.7	85/28ft	120°	√				185
Aurora 3 Gen 1 White LED Modules		3	3	100	300	7500K	68	0.96	62/20.6ft	120°	√				185
Aurora Mini White LED Modules	√	2	4	42.5	170	7500K	66	0.6	100/25ft	120°	√				185
Aurora Mini Red LED Modules	√	2	4	8.75	35	RED	67	0.5	120/30ft	120°	√				185
WOW White LED Modules	√	3	2	70	140	7500K	67	0.72	83/41.5ft	160°	√	√			185
WOW Red LED Modules		3	2	17.5	35	Red	67	0.5	120/60ft	160°	√	√			185
AnPro White LED Modules	√	2	2	110	220	7500K*	67	1.2	50/25ft	1602°	√	√			186
AnPro180 White LED Modules	√	2	1.5	120	180	7500K*	67	1.2	50/75ft	180°	√	√			186
Trident White LED Sign Box Mod. Double-sided	√	3	1/sf	420	210/sf	7500K	66	4.5	13/13ft	160°	√	√			186
Enterprise White LED Modules		8	1	735	327.5	7500K	67	7	8	180°		√			186
ArRay Pro White LED Sign Box Mod. Double-sided		6	3/sf	360	1080	7500K	67	3.6	16ft	120°		√	√		186
ArRay Eco White LED Sign Box Mod. Double-sided		6	3/sf	190	570	7500K	67	1.8	33	120°		√	√		186
ArRay SF White LED Sign Box Mod. Single-sided		3	3/sf	105	315	7500K	67	1	60ft	160°		√	√		186
AnPro180 LED Stick Fluorescent Lamp Replacements		N/A	3/ft	N/A	V	7500K	67	V*	V	180°		√	√	√	187
AuroraFlex LED Tubing		N/A	N/A	N/A	V	V	65	V	V	270°		√	√	√	188
AuroraFlex Mini LED Tubing		N/A	N/A	N/A	V	V	65	V	V	240°		√	√	√	188
<b>PRINCIPAL LED</b>															
Street Fighter White LED Modules	√	3	1.6	75	120	7000K	67	0.72	80/50ft	160°	√	√			189
Street Fighter Plus White LED Modules		3	1.8	72	130	7000K	67	0.72	80/44ft	160°	√				189
Street Fighter Slim White LED Modules		1	3.8	55	212	7000K	67	0.72	80/21ft	170°	√	√			189
Street Fighter HeavyWeight White LED Modules		3	1.8	125	225	7000K	67	1.32	45/25ft	160°	√	√	√	√	189
Street Fighter Mini White LED Modules		2	4.5	20	90	7000K	67	0.32	180/40ft	120°	√				189
Street Fighter Colors LED Modules		3	1.8	V	V	R, B, G, OR	67	0.65	90/50ft	160°	√				189
Street Fighter Mini Colors LED Modules		2	4.5	V	V	V	67	V	V	120°	√				189
Street Fighter MiddleWeight White LED Modules		2	2.25	72	162	7000K	67	0.72	80/35ft	160°	√	√	√	√	190
Street Fighter POD White LED Modules		1	2.25	110	247.5	7000K	67	1.32	44/19.55	30x15°		√			190
Street Fighter Knockout White LED Module		3	1/2ft	550	225	7000K	68	7	8 mod	180°		√			190
Street Fighter RGB LED Modules		3	1.8	V*	V*	V*	67	6.5	90/50ft	160°	√				190
Light Tape Pure White LED Outdoor		N/A	300/reel	N/A	150	6300K	67	V	16.4ft/reel	120°		√		√	190
Light Tape Pure White LED Indoor		N/A	600/reel	N/A	300	6300K	65	V	16.4ft/reel	120°		√		√	190
Fusion 2 Sign White LED Modules		3	2	80	160	6500K	66	0.75	80/40ft	170°	√				191
Fusion 3 Sign White LED Modules		3	3	80	240	6500K	66	0.75	78/26ft	170°	√				191
Fusion 2 Red LED Modules		3	2	14	28	Red	66	0.6	50/25ft	170°	√				191
Fusion 3 Red LED Modules		3	3	12	37	Red	66	0.6	33/11ft	170°	√				191
Fusion Freedom LED Modules		1	2	V*	V*	6500K	66	V*	V*	V*	√				192
Fusion Freedom LED Modules - Colors		1	2	V*	V*	V*	66	V*	V*	V*	√				192
Qwik MOD 1 LED Modules		1	2.5	44	110	7100K	68	0.4	150/60ft	170°	√	√	√	√	191
Qwik MOD 2 LED Modules		2	1.7	88.2	150	7100K	68	0.8	76/44.7ft	170°	√	√	√	√	191
Qwik MOD 3 LED Modules		3	1.5	133	200	7100K	68	1.2	150/33.3ft	170°	√	√	√	√	191
Qwik MOD 4 LED Modules		4	1.5	173	260	7100K	68	1.6	38/25.5	170°	√	√	√	√	191
Tap Out Stik LED Fluorescent Lamp Replacements	√	N/A	N/A	N/A	V	7000K	67	V	V	160°		√	√	√	194
Qwik Stik LED Fluorescent Lamp Replacements		N/A	N/A	N/A	V	6300K	66	V	V	120°		√	√	√	193

# LED GUIDE

✓ - Yes

All 12 VDC unless noted

\* Multiple options V- varies per color/length

	Top Sellers	LEDs / module	Modules / ft / sqft	Lumens / module	Lumens / ft / sqft	Color Temp / Colors	IP Rating	W / Module	Modules/ft per 60 W Power Supply	Viewing Angle	Channel Letters	Cabinet Lighting	Fluorescent Replacement	Catalog Page
<b>US LED</b>	<b>PROPERTIES</b>										<b>APPLICATIONS</b>			
US LED Point4 White LED Modules	✓	3	3	50	150	6300K	66	0.66	90/30ft	120°	✓			196
US LED Plus Saver Red LED Modules 2 UP		2	3	7	21	Red	66	0.33	180/60ft	120°	✓			196
US LED Plus Saver Red LED Modules 3 UP		3	2	10.5	21	Red	66	0.35	170/85ft	120°	✓			196
US LED Right Light Red LED Modules 2 UP		2	3	14	42	Red	66	0.66	90/30ft	120°	✓			196
US LED Right Light Red LED Modules 3 UP		3	2	21	42	Red	66	0.65	92/46ft	120°	✓			196
US LED Saver3 White LED Modules		3	2	50	100	6300K	66	0.66	120/30ft	120°	✓			196
US LED Tandem2 Single-Sided Cabinet Modules 24VDC		6	2	112	225	6300K	66	1.5	50/25ft	120°		✓	✓	197
USLED Tandem2 Double-Sided Cabinet Modules 24VDC		12	2	225	450	6300K	66	3	24/12ft	120°		✓	✓	197
<b>ALLANSON LED</b>	<b>PROPERTIES</b>										<b>APPLICATIONS</b>			
StormTight II Low Profile LED Modules		2	3	39	117	6700K	67	0.48	100/33ft	155°	✓			198
StormTight LED 3 Watt Modules		3	0.75	427	320	6300K	67	3.8	14/10.5ft	155°		✓	✓	198
LEDrofit		N/A	N/A	V	V	6000K	67	V	V	N/A		✓	✓	198

## LED Power Supply Chart

	Top Sellers	Input Volts	Output Volts	Watt	Output Legs	IP Rating	Catalog Page
<b>LED POWER SUPPLIES</b>	<b>PROPERTIES</b>						
Allanson CV125120277	✓	120 - 277	12 VDC	60	1	IP67	199
Allanson CV12125MV		120 - 277	12 VDC	2x60	2x60	IP67	199
Allanson CVW125MV		120 - 277	12 VDC	60	1	IP68	199
Principal LED PL6012U	✓	120 - 277	12 VDC	60	1	IP67	195
Principal LED PL6012PCMU		120 - 277	12 VDC	60	1	IP67	195
Principal LED PL6012MU		120 - 277	12 VDC	60	1	IP67	195
Principal LED PL12012U		120 - 277	12 VDC	120	2x60	IP67	195
Principal LED PL2012PCMU		100 - 277	12 VDC	20	1	IP67	195
Principal LED PLMV26412 Non Class 2		120 - 277	12 VDC	264	1	IP67	195
US LED / Advance PSA1260	✓	120	12 VDC	60	1	IP66	197
US LED / Advance PSA1260120277V		120 - 277	12 VDC	60	1	IP66	197
US LED / Advance PSA1212		120	12 VDC	12	1	IP66	197
US LED / Advance PSA2480 24 VDC		120	24 VDC	80	1	IP66	197
US LED / Advance PSA24100 24 VDC		120 - 277	24 VDC	100	1	IP66	197
Universal L12V60UNVA		100 - 277	12 VDC	60	1	IP66	199
Universal L12V60UNVQ Wet Location		120 - 277	12 VDC	60	1	IP67	199
France LED1260 WMPS Wet Location	✓	120 - 277	12 VDC	60	1	IP67	200
France LED 1260MMP		120 - 277	12 VDC	60	1	IP67	200