

# Product Bulletin

## Concept® 234 Fabric Wall Film

Concept® 234 is a 7.0 mil premium white matte coated polyester fabric with an acrylic removable pressure sensitive adhesive backed by a 90# sta flat liner. The combination of fabric and adhesive allows removability of this product from normal wall surfaces. The 90# release liner provides excellent stability for processing using standard solvent, eco-solvent, UV curable and latex digital inks common to wide format digital printing systems.

Applications	Concept® 234 is designed for temporary application of decals and graphics to most types of painted interior walls. This includes most flat, semi gloss and gloss paint finishes. Decals may also be applied to sealed wall coverings. The surface must be smooth and clean prior to application. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces.		
Thickness	Film	7.0 mils.	
	Adhesive	.8 to 1.2 mils.	
	Liner	6.7 mils.	
	(Thickness variation +/- 10%)		
Dimensional Stability	Good.		
Temperature Ranges	Minimum application temperature	+40°F.	
	Service temperature	-40°F to +200 F.	
Ignition Properties	ASTM D1929		
	Flash Ignition Temperature	752°F	400°C
	Self Ignition Temperature	788°F	420°C
Removability	Removable up to 6 months under normal interior exposure conditions and applications. Removal of wall fabric should be done at a 180° angle while pulling slowly against itself.		
Adhesion	To standard test panels	4 to 12 oz. /in.	
	Tested according to PSTC-101 Method A procedures with 24 hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.		
Storage Stability	6 months shelf life when stored at 70°F and 50% relative humidity.		
Product Code	Concept® 234-54	54" x 100'	
	Concept® 234-60	60" x 100'	
Recommendations	Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in product failure.		



***Manufacturer of Pressure Sensitive Films,  
Traffic Graffix Floor Advertising Films,  
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.