

# ALPHA

sign products by wensco

## 6 mil WD6 Calendered Permanent Print Media

		WD6MP54150	WD6GP54150		
<b>Physical Properties</b>				<b>Conditions for Use</b>	
<b>Finish</b>		Matte	Gloss	<b>Shelf Life</b>	1 year
<b>Color</b>		White	White	<b>Outdoor Durability</b>	Up to 3-5 years
<b>Adhesive</b>		Permanent: High Tack, High-Peel, Clear	Permanent: High Tack, High-Peel, Clear	<b>Min Application Temp</b>	35° F (1.6° C)
<b>Film</b>		Calendered Vinyl	Calendered Vinyl	<b>Service Temp Range</b>	-20° to 150° F (-28.9° to 65.6° C)
<b>Liner</b>		90# Layflat	90# Layflat	<b>Solvent Resistance</b>	Excellent
<b>Opacity</b>		95% Minimum	100%	<b>Water Resistance</b>	Excellent
<b>Gloss Level</b>		8% Typical	90% Typical		
<b>Thickness</b>	<b>Film</b>	5.5 ± 0.2 mil	5.5 ± 0.2 mil		
	<b>Film w/ adhesive</b>	6.5 ± 0.2 mil	6.5 ± 0.2 mil		
	<b>Total thickness</b>	13.0 ± 0.4 mil	13.0 ± 0.4 mil		
<b>Adhesion</b>	<b>SS 15 min Room Temp Dwell</b>	65 oz/in minimum	65 oz/in minimum		
	<b>SS 24 hr Room Temp Dwell</b>	80 oz/in minimum	80 oz/in minimum		
<b>Weight</b>	<b>Film w/Adhesive</b>	220-225 gsm	215-220 gsm		
	<b>Total w/liner</b>	370-380 gsm	360-370 gsm		
<b>Printability</b>		Latex, UV Inkjet, Eco-Solvent, Solvent	Eco-Solvent/Solvent, Latex and UV		



The information provided herein is correct to the best of Wensco's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.