



ESR2048-46

APPLICATION and PERFORMANCE SPECIFICATION

Electronic ballast for (6/5/4) T12HO lamps up to 8ft long. 20 feet to 48 feet total length. Electronic ballast for (6/5/4) T8HO lamps up to 6ft long. 24 feet to 36 feet total length.

- Line Voltage: 120 to 277 vac, ±10%, 50/60Hz
- Series Lamp Operation

Rapid Start Operation

Active Power Factor Correction

	*60 Hz data									
	Lamp		Lamp Footage			Max Input	Nominal			
					Volts	Power	Line Current	Power	THD	Crest
	Туре	#	Min	Max		(Watts)	(Amps)	Factor		Factor
	T12HO	6,5,4	20	48	120	425	3.50	>.90	<10%	<1.7
	T12HO	6,5,4	20	48	277	415	1.50	>.90	<10%	<1.7
	T8HO	6,5,4	24	36	120	380	3.16	>.90	<10%	<1.7
	T8HO	6,5,4	24	36	277	372	1.34	>.90	<10%	<1.7

Application and Performance Specification Information Subject to Change without Notification.

THD < 15% @ 277volts 42ft and under.

Performance:

- Meets ANSI Standard C82.11-2011
- Meets ANSI Standard C62.41-2002
- Meets FCC Part 18 (Class A) for EMI and RFI non-consumer limits

Application:

Minimum Starting Temperature:	-20° F, -29° C		
Energy Saving Lamps:	60° F, 16° C		
 Maximum Case Temperature: 	176° F, 80° C		
 Sound Rated: 	А		

Safety:


- No PCB's
- $_{\rm C}\rm UL_{\rm US}$ Listed
- (Class P, Type HL, Type 2 Outdoor)
- cCSAus Listed


Physical Parameters:

 Length: 	16.7"
Width:	3.15"
 Height: 	1.2"
 Weight: 	4.85 lbs
 Carton Quantity: 	1 piece
 Lead length: 	Black, White 25" (± 1")
-	Red, Blue, Yellow, Orange 72" (± 1")
	Blue/ White, Brown, Orange/ Black 72" (± 1")

Warranty:


Universal Lighting Technologies warrants to the purchaser that each electronic ballast will be free from defects in materialor workmanship for a period of 4 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.





For five lamp operation, individually cap yellow leads. Insulate to 600Volts

Ballast case must be grounded. Manufactured in China.



For two lamp operation, individually cap brown and yellowleads. Insulate to 600Volts

