

# 111

## HAND-CUT STENCIL

### DESCRIPTION

Hand-cut, high quality, durable stencil coated with an advanced medium tack, rubber-based pressure-sensitive adhesive protected by an easy-release-treated HDPE liner. Designed for superior shape carving in marble and granite. Unique rubber formula allows easy cutting with less frequent knife sharpening. Controlled shrinkage gives accurate panel replacement after frosting. Recommended for maximum depth glass etching.

### PRODUCT APPLICATIONS

For optimum performance, use with #211 Stencil Filler.

### STANDARD SIZES:

12.75" x 10 yards  
18.75" x 10 yards  
21" x 10 yards  
25" x 10 yards  
30" x 10 yards  
30.50" x 10 yards



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/15

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

|   |                      |
|---|----------------------|
| <b>Adhesive</b>                                   | Medium Tack / Rubber |
| <b>Total Thickness</b> (mils)<br>PSTC-133         | 48 (1.22mm)          |
| <b>Tensile Strength</b> (lbs/in)<br>PSTC-131      | 5 (21.9 N/25mm)      |
| <b>180° Adhesion to Steel</b> (oz/in)<br>PSTC-101 | 17.5 (4.8 N/25mm)    |
| <b>Elongation</b> (% at break)<br>PSTC-131        | 300                  |



800.253.1569 | [wensco.com](http://wensco.com)

