

Street Stik Series

# STREET STIK™ SERIES

The industry's first retrofit solution for shallow cabinets



## SPECIFICATIONS

Beam Angle	160° Low Dome Batwing Optic	
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs	
Dimensions	SS: 0.6"W x .71"H x Length	DS: 0.6"W x 1.0"H x Length
Efficacy	Cool White	95 LM/W
	True White	95 LM/W
	Natural White	95 LM/W
	Warm White	95 LM/W
Fastening	Socket (retro) / Brackets (new)	
Input	12VDC	
Intensity	Cool White	125 LM/ft
	True White	125 LM/ft
	Natural White	125 LM/ft
	Warm White	125 LM/ft
Max Mods (Series)	N/A	
Operating Temp	-40° to +60°C	
Packaging	SS/HD: 10 pieces per tube	DS/HD: 8 pieces per tube
Power (Watts)	See Product Options	
Power Supply	P-LED 12VDC	
Protection Grade	IP67	
Stiks per PS	See Product Options	
Spacing	See Product Options	
Warranty	5 Year Product / 5 Year Limited Labor	

## FEATURES

- Street Fighter Heavyweight™ modules pre-assembled onto a direct socket mount extrusion
- Get even more lumen output with the Street Stik HD™
- Available in all traditional T-12 lamp lengths from 8"-120" and fits directly into T-12 sockets
- Match CCT with any other Street Fighter product for a consistent color across all signage
- Modules and extrusion can be purchased separately



## WIRING DETAILS

White/Red	Positive
White/Black	Negative


## RECOMMENDED COVERAGE CHART

Depth from Stik to Face	Estimated Spacing between Stiks
5"	10"
6"	12"
7" – 8"	16"
9" – 12"	18"

>12 (Use two banks Single-Sided)

Note: Product and depth may vary depending on face material and desired brightness.

Ask about our Qwik Stik Mounting Brackets for new construction jobs





## Street Stik Single-Sided™

### PRODUCT OPTIONS

T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Stiks per 60W PS	Stiks per 120W PS	Part Number*
18"	15.91"	375	3.0	3.96	15.0	30.0	PL-OP2-HW3-P/ST-SS-18-XX
24"	21.91"	375	3.0	3.96	15.0	30.0	PL-OP2-HW3-P/ST-SS-24-XX
30"	27.91"	500	4.0	5.28	11.0	22.0	PL-OP2-HW3-P/ST-SS-30-XX
36"	33.91"	625	5.0	6.60	9.0	18.0	PL-OP2-HW3-P/ST-SS-36-XX
42"	39.91"	750	6.0	7.92	7.0	14.0	PL-OP2-HW3-P/ST-SS-42-XX
48"	45.91"	875	7.0	9.24	6.0	12.0	PL-OP2-HW3-P/ST-SS-48-XX
60"	57.91"	1000	8.0	10.56	5.0	10.0	PL-OP2-HW3-P/ST-SS-60-XX
64"	61.91"	1125	9.0	11.88	5.0	10.0	PL-OP2-HW3-P/ST-SS-64-XX
72"	69.91"	1250	10.0	13.20	4.0	8.0	PL-OP2-HW3-P/ST-SS-72-XX
84"	81.91"	1500	12.0	15.84	3.0	6.0	PL-OP2-HW3-P/ST-SS-84-XX
96"	93.91"	1750	14.0	18.48	3.0	6.0	PL-OP2-HW3-P/ST-SS-96-XX
108"	105.9"	1875	15.0	19.80	3.0	6.0	PL-OP2-HW3-P/ST-SS-108-XX
117"	114.91"	2125	17.0	22.44	2.0	4.0	PL-OP2-HW3-P/ST-SS-117-XX
120"	117.91"	2125	17.0	22.44	2.0	4.0	PL-OP2-HW3-P/ST-SS-120-XX

\*XX=WW (3500K Warm White), NW (5000K Natural White), TW (7000K True White), CW (9000K Cool White)

## Street Stik Double-Sided™

### PRODUCT OPTIONS

T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Stiks per 60W PS	Stiks per 120W PS	Part Number*
18"	15.91"	750	6.0	7.92	7.5	15.0	PL-OP2-HW3-P/ST-DS-18-XX
24"	21.91"	750	6.0	7.92	7.5	15.0	PL-OP2-HW3-P/ST-DS-24-XX
30"	27.91"	1000	8.0	10.56	5.5	11.0	PL-OP2-HW3-P/ST-DS-30-XX
36"	33.91"	1250	10.0	13.20	4.5	9.0	PL-OP2-HW3-P/ST-DS-36-XX
42"	39.91"	1500	12.0	15.84	3.5	7.0	PL-OP2-HW3-P/ST-DS-42-XX
48"	45.91"	1750	14.0	18.48	3.0	6.0	PL-OP2-HW3-P/ST-DS-48-XX
60"	57.91"	2000	16.0	21.12	2.5	5.0	PL-OP2-HW3-P/ST-DS-60-XX
64"	61.91"	2250	18.0	23.76	2.5	5.0	PL-OP2-HW3-P/ST-DS-64-XX
72"	69.91"	2500	20.0	26.40	2.0	4.0	PL-OP2-HW3-P/ST-DS-72-XX
84"	81.91"	3000	24.0	31.68	1.5	3.0	PL-OP2-HW3-P/ST-DS-84-XX
96"	93.91"	3500	28.0	36.96	1.5	3.0	PL-OP2-HW3-P/ST-DS-96-XX
108"	105.9"	3750	30.0	39.60	1.5	3.0	PL-OP2-HW3-P/ST-DS-108-XX
117"	114.91"	4250	34.0	44.88	1.0	2.0	PL-OP2-HW3-P/ST-DS-117-XX
120"	117.91"	4250	34.0	44.88	1.0	2.0	PL-OP2-HW3-P/ST-DS-120-XX

\*XX=WW (3500K Warm White), NW (5000K Natural White), TW (7000K True White), CW (9000K Cool White)

## Street Stik Series



## Street Stik HD Single-Sided™

## PRODUCT OPTIONS

T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Stiks per 60W PS	Stiks per 120W PS	Part Number*
18"	15.91"	500	4.0	5.28	11.0	22.0	PL-OP2-HW3-P/ST-SS-18-XX (HD)
24"	21.91"	500	4.0	5.28	11.0	22.0	PL-OP2-HW3-P/ST-SS-24-XX (HD)
30"	27.91"	750	6.0	7.92	7.0	14.0	PL-OP2-HW3-P/ST-SS-30-XX (HD)
36"	33.91"	875	7.0	9.24	6.0	12.0	PL-OP2-HW3-P/ST-SS-36-XX (HD)
42"	39.91"	1000	8.0	10.56	5.0	10.0	PL-OP2-HW3-P/ST-SS-42-XX (HD)
48"	45.91"	1000	8.0	10.56	5.0	10.0	PL-OP2-HW3-P/ST-SS-48-XX (HD)
60"	57.91"	1500	12.0	15.84	3.0	6.0	PL-OP2-HW3-P/ST-SS-60-XX (HD)
64"	61.91"	1500	12.0	15.84	3.0	6.0	PL-OP2-HW3-P/ST-SS-64-XX (HD)
72"	69.91"	1625	13.0	17.16	3.0	6.0	PL-OP2-HW3-P/ST-SS-72-XX (HD)
84"	81.91"	1875	15.0	19.80	3.0	6.0	PL-OP2-HW3-P/ST-SS-84-XX (HD)
96"	93.91"	2250	18.0	23.76	2.0	4.0	PL-OP2-HW3-P/ST-SS-96-XX (HD)
108"	105.9"	2375	19.0	25.08	2.0	4.0	PL-OP2-HW3-P/ST-SS-108-XX (HD)
117"	114.91"	2500	20.0	26.40	2.0	4.0	PL-OP2-HW3-P/ST-SS-117-XX (HD)
120"	117.91"	2625	21.0	27.72	2.0	4.0	PL-OP2-HW3-P/ST-SS-120-XX (HD)

\*XX=WW (3500K Warm White), NW (5000K Natural White), TW (7000K True White), CW (9000K Cool White)

## Street Stik HD Double-Sided™

## PRODUCT OPTIONS

T-12	Actual Length	Lumens per Stik	No. of Mods	Watts	Stiks per 60W PS	Stiks per 120W PS	Part Number*
18"	15.91"	1000	8.0	10.56	5.5	11.0	PL-OP2-HW3-P/ST-DS-18-XX (HD)
24"	21.91"	1000	8.0	10.56	5.5	11.0	PL-OP2-HW3-P/ST-DS-24-XX (HD)
30"	27.91"	1500	12.0	15.84	3.5	7.0	PL-OP2-HW3-P/ST-DS-30-XX (HD)
36"	33.91"	1750	14.0	18.48	3.0	6.0	PL-OP2-HW3-P/ST-DS-36-XX (HD)
42"	39.91"	2000	16.0	21.12	2.5	4.0	PL-OP2-HW3-P/ST-DS-42-XX (HD)
48"	45.91"	2000	16.0	21.12	2.5	4.0	PL-OP2-HW3-P/ST-DS-48-XX (HD)
60"	57.91"	3000	24.0	31.68	1.5	2.0	PL-OP2-HW3-P/ST-DS-60-XX (HD)
64"	61.91"	3000	24.0	31.68	1.5	2.0	PL-OP2-HW3-P/ST-DS-64-XX (HD)
72"	69.91"	3250	26.0	34.32	1.5	2.0	PL-OP2-HW3-P/ST-DS-72-XX (HD)
84"	81.91"	3750	30.0	39.60	1.5	2.0	PL-OP2-HW3-P/ST-DS-84-XX (HD)
96"	93.91"	4500	36.0	47.52	1.0	2.0	PL-OP2-HW3-P/ST-DS-96-XX (HD)
108"	105.9"	4750	38.0	50.16	1.0	2.0	PL-OP2-HW3-P/ST-DS-108-XX (HD)
117"	114.91"	5000	40.0	52.80	1.0	2.0	PL-OP2-HW3-P/ST-DS-117-XX (HD)
120"	117.91"	5250	42.0	55.40	1.0	2.0	PL-OP2-HW3-P/ST-DS-120-XX (HD)

\*XX=WW (3500K Warm White), NW (5000K Natural White), TW (7000K True White), CW (9000K Cool White)