"Thermo Tack" 'Adhesive' Sublimation Paper for Apparel

TexPrint

'Thermo-Tack' Tackified Coating Chemistry provides:

- A unique print medium engineered solely for apparel sublimation transfer applications
- A tacky super-uniform coated print surface activates during the transfer process
- High fluid capacity. Thermo-Tack paper maintains sharp definition even at heaviest ink-loads
- Absolute color consistency
- 100 gsm base sheet for ease of handling right through the calendar machine
- Special sizes are available upon request

Compatible with:

- Bordeaux, Sawgrass, Sensient, J-Teck, Epson & Kiian inks
- Roland, Epson, Mutoh and Mimaki printers
- Most polyester fabrics

Best output is attained with properly profiled integration. Assistance to achieve optimum output is available upon request!

Available in:

- 24" (61 cm)
- 36" (91 cm)
- 44" (1.11 m)
- 54" (1.37 m)
- 64" (1.62 m)
- 72" (1.82 m)

TexPrint[®]TT is available through authorized distributors worldwide.

Sublimation Paper

Thermo Tack Adhesive

Special sizes available upon request.



2420 Tech Center Parkway • Building 140 • Lawrenceville, Georgia 30043 USA • (770) 935-5080 • www.beaverpaper.com

Spec Sheet





"Thermo Tack" Adhesive Sublimation Paper

TexPrint[®] Thermo-Tack -- 100 gsm -- Water Based Sublimation

Recommended use and applications **APPAREL TEXTILE SUBSTRATE**

Clam Shell Heat Presses

Custom Athletic Wear, Performance Wear, Cycling, Ski Wear, Wrestling, Volley Ball,

Baseball, Hockey, Lacrosse, Soccer, Cheer, Football, Track & Field

Key Features of TexPrint® Thermo Tack

- Tackified adhesive coating is activated with heat
- Adheres to more polyester textiles
- Eliminates ghosting caused by flatbed heat presses
- Reduces waste of prints and fabrics
- High transfer yield

pson – Roland – Mimaki – Mutoh	TexPrint ^{®TT}		Adhesive Paper			100 gsm	
	Code #	Width	Core	Length	rolls/box	rolls/pallet	lb/roll
	TPTKY-24-275-3	24" - 61 cm	3"-76 mm	275 ft - 84 m	1	48	13
	TPTKY-24-393-3	24" - 61 cm	3"-76 mm	393 ft - 120 m	1	48	18
	TPTKY-36-275-3	36" - 91 cm	3"-76 mm	275 ft - 84 m	1	36	19
	TPTKY-36-393-3	36" - 91 cm	3"-76 mm	393 ft - 120 m	1	36	27
	TPTKY-44-275-3	44" - 1.1 m	3"-76 mm	275 ft - 84 m	1	36	23
	TPTKY-44-393-3	44" - 1.1 m	3"-76 mm	393 ft - 120 m	1	36	32
	TPTKY-54-393-3	54" - 1.37 m	3"-76 mm	393 ft - 120 m	1	36	28
	TPTKY-60-393-3	60" - 1.52 m	3"-76 mm	393 ft - 120 m	1	36	44
	TPTKY-64-393-3	64" - 1.63 m	3"-76 mm	393 ft - 120 m	1	36	47
Щ	TPTKY-72-393-3	72" - 1.82 m	3"-76 mm	393 ft - 120 m	1	24	53

For use with water based digital dye-sublimation inks. Optimal performance achieved with custom ICC profiles. Profiling assistance is available through select distributors.