

## PRODUCT DESCRIPTION

BF METALLIC series consists of polyurethane films characterized by a pearlescent finishing with an iridescent effect. The cutting line of all the films is highly visible and the workability of the product is unique; its polyester adhesive carrier allows for fast weeding and easy repositioning of any small details that might have accidentally lifted from the carrier.

The BF METALLIC series is suitable for multilayer applications and is resistant to washing up to 40°C. The colors available allow it to be used for application on sporty and fashion clothing.

## APPLICATION TECHNIQUES

- Knockout
- Multi-layer
- Layering with other series

## APPLICATION STEPS

- Cut - 45° blade
- Weed excess material
- Turn on your heat press - heat to 140°C/285°F
- Place your graphic on the garment
- Press it - 140°C/285°F for 12 seconds
- Remove the liner - hot

## SIZES





<b>H 50 cm</b>	L 25 mt / 12,5mt / 5 mt / 1 mt
<b>H 75 cm</b>	L 25 mt (upon request)
<b>H 100 cm</b>	L 25 mt (upon request)
<b>H 150 cm</b>	L 25 mt (upon request)

Comply with regulation **REACH** n°1907/2006/EU




## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev\_2021/03






## TECHNICAL DATA

	Film: PU/polyurethane
	Thickness: 90μ (±5%)
	Liner: adhesive PET
	Finish: gloss

## PLOTTER SETTING

	Cut settings: mirror
	Blade: 45°
	Minimum cut: 0,3 cm

## APPLICATION

	Temperature: 140°C - 285°F
	Time: 12''
	Liner removal: hot
	Pressure: medium - 3,5 bar - 50 PSI
	Textile: organic, synthetic, mixed

## WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	40°C - 104°F
Dry clean	✓
Dryer	✗

**BF METALLIC**

**COLOUR GUIDE**



- Pearlescent finishing with an iridescent effect
- Ability to cut small details
- Easy to work



**BF M700A**  
WHITE METALLIC



**BF M730A**  
RED METALLIC



**BF M738A**  
CYCLAMEN METALLIC



**BF M742A**  
BLUE METALLIC



**BF M751A**  
ACID GREEN METALLIC

