

# TECHNICAL DATA SHEET

## GF 218 WINDOWMARK™ BLOCKOUT

8.0 MIL GLOSS WHITE DUAL-LAYER VINYL  
CLEAR REMOVABLE ADHESIVE

GF 218 WindowMark™ Blockout is an 8.0 mil gloss white print media with dual-layer construction. GF 218 is designed to be 100% opaque and is excellent for window graphics & retail displays where total opacity and zero light transmission is required. GF 218 WindowMark™ Blockout is outdoor durable for up to three years and the clear removable adhesive is ideal for short-term promotions where clean removability is required.

PRODUCT NAME	218
<b>FILM</b>	
Film Type	White Monomeric Vinyl
Film Thickness (mils/μm)	7.0 / 178 (+/- 10%)
Film Weight (gsm)	248
Gloss (60°)	≥70
Opacity (%)	100
Tensile Strength (lbs/in)	MD ≥ 3000 / CD ≥ 3000
Elongation (%)	MD ≥ 225 / CD ≥ 225
Dimensional Stability (FTM 14)	MD ≤ 0.90 mm / CD ≤ 0.90 mm
<b>ADHESIVE</b>	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils/μm)	0.8-1.0 / 20-25
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	2.3 / 11
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	3.0 / 13
Peel Strength on Glass (lbs/in) / (N/25mm) 15 min	2.7 / 12
Peel Strength on Glass (lbs/in) / (N/25mm) 24 hrs	2.9 / 13
<b>LINER</b>	
Liner Weight (#/gsm)	90 / 145
Liner Type	White 2-Sided PE Coated Kraft
Liner Thickness (mils/μm)	6.7 / 170
Release Force @ 300" / min (g/2")	120-150
<b>PERFORMANCE GUIDANCE</b>	
Application Temperature	≥ +40 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	up to 3 years
Removability (under normal conditions)	1 year Clean Removability

# TECHNICAL DATA SHEET

## GF 218 - 8.0 MIL GLOSS WHITE DUAL-LAYER VINYL CLEAR PERMANENT ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p><b>APPLICATION</b></p> <ul style="list-style-type: none"> <li>● WET APPLY</li> <li>● DRY APPLY</li> <li>○ LAMINATING</li> <li>○ MOUNTING</li> <li>● DIE CUTTABLE</li> <li>○ HOT STAMP</li> <li>○ THERMAL DIE</li> <li>● FLATBED CUTTABLE</li> </ul>	<ul style="list-style-type: none"> <li>● POP/RETAIL</li> <li>○ WALL</li> <li>○ WRAP</li> <li>● WINDOW</li> <li>○ FLOOR</li> <li>○ TRANSLUCENT</li> <li>○ FLEET</li> <li>● GENERAL SIGNAGE</li> <li>● OUTDOOR</li> </ul>	<ul style="list-style-type: none"> <li>● SOLVENT</li> <li>● ECO-SOLVENT</li> <li>● LATEX</li> <li>● UV CURABLE</li> <li>● SCREEN</li> <li>● OFFSET (UV CURABLE)</li> <li>○ OFFSET (CONVENTIONAL)</li> </ul>
<p><b>SUBSTRATES</b></p> <ul style="list-style-type: none"> <li>● OEM PAINTED METAL</li> <li>● PAINTED ALUMINUM</li> <li>● STAINLESS STEEL</li> <li>○ LOW-ENERGY SURFACES</li> <li>● GLASS</li> </ul>		

### FAQS

Can you use the film just as a block-out vinyl?	Yes. GF 218 WindowMark Blockout™ is an excellent choice because it is 100% “blockout”. The removable adhesive also makes for easy, clean removal. This can be used on store front windows and internal windows where total privacy is a must.
Can you use this vinyl for reverse print window decals or graphics?	Yes. Reverse print on a clear vinyl like GF 206 or GF 255. Then print on the GF 218 (Right read) and laminate the two films together. Trim and apply the film on the inside of the window for a “Push Pull” type decal or graphic.
Can this vinyl be contour cut?	Yes. GF 218 WindowMark Blockout™ can be contour cut for medium to larger graphics. This vinyl is not intended to be used for print and cut letters. The ideal applications are decals and window graphics where zero light transmission is required.