

ULTRA TRANSLUCENT PRODUCT CODE: 3-2085



PRODUCT DESCRIPTION

This 3.2-mil flexible translucent white vinyl is an intermediate vinyl designed with a special adhesive featuring a good balance of tack, peel and shear. This is an excellent choice for interior and exterior backlit graphic applications.

APPLICATIONS

- Point of purchase displays
- Trade show displays
- Product identification

FEATURES AND BENEFITS

- Translucent flexible vinyl ideal for backlit graphic applications.
- Can be wet applied

TECHNICAL DATA

Face Material	3.2-mil flexible translucent vinyl
Color and Finish	White matte
Adhesive	530UV, Medium tack permanent solvent with ultraviolet light inhibitor
Liner	72# poly coated bleached

TYPICAL CHARACTERISTICS

Target Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	5.1 lbs./inch	6.4 lbs./inch
Shear	100+ hours	
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability	5 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.



800.253.1569 | wensco.com