# **ULTRA DRY ERASE PRODUCT CODE:** 4-0591



## PRODUCT DESCRIPTION

1.0-mil gloss clear polyester overlaminate. The face film has a dry-erase coating for longer-term dry-erase capabilities.

#### **APPLICATIONS**

- Make any printed sign dry-erase
- Gloss overlaminate to protect printed images

## **FEATURES AND BENEFITS**

- Dry-erase overlaminate with longer-term capabilities
- Make any printed sign dry-erase
- Please refer to our <u>Dry-Erase Marker Compatibility Guidelines</u> for additional details
- Menu boards and business presentations

#### TECHNICAL DATA

Face Material 1.0-mil polyester Color and Finish Clear gloss

Adhesive 530, Permanent solvent Liner 78# bleached paper

#### TYPICAL CHARACTERISTICS

Target Adhesion Values	<u>15 min.</u>	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	30 oz.	40 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to $+180$ °F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability (ASTM G53)	1 year	

## **CHEMICAL RESISTANCE**

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

