ULTRA SEMI GLOSS WHITE STANDARD PRODUCT CODE: 3-9466



PRODUCT DESCRIPTION

3.5-mil premium calendered vinyl consists of a flexible, semi-gloss film having excellent weathering and aging characteristics. Used for decorative striping, transportation makings, product identification and warning decals. High-tack adhesive for low energy surfaces such as hard to adhere to plastics.

APPLICATIONS

- Decorative striping
- Transportation markings
- Product identification
- Warning decals

FEATURES AND BENEFITS

• Suitable for low surface energy substrates.

TECHNICAL DATA

Face Material	3.5-mil premium calendered vinyl
Color and Finish	Semi-gloss white
Adhesive	14, high-tack permanent solvent 2-mils
Liner	90# polycoated bleached layflat

TYPICAL CHARACTERISTICS

Target Adhesion Values	<u>15 min</u> .	<u>24 hr.</u>
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	141 oz.	154 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability	5 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	
Detergent (24 hr)	
10% HCl (10 min)	
10% Ammonium Hydroxide (10 min)	
Anti-Freeze (24 hr)	
SAE 20 Motor Oil (24 hr)	
Gasoline (1 hr)	

No Effect No Effect No Effect No Effect No Effect No Effect No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

