

CLASSIC HIGH GLOSS HIGH BOND BO LOGO

PRODUCT CODE: 4-2168



PRODUCT DESCRIPTION

A 3-year outdoor durable high gloss white vinyl media with permanent High Bond Gray adhesive for mounting to boards and other hard to adhere to substrates. Excellent for use on Acrylic, Diebond®, Sintra®, Gatorplast™, Gatorfoam®, Steel and painted dry wall for medium-term promotional, point of purchase, trade show displays, outdoor signage and banners.

APPLICATIONS

- Point of purchase displays
- Trade show displays
- Hard to adhere to substrates
- Permanent wall graphics
- Print and cut graphics

FEATURES AND BENEFITS

- 3-year outdoor durable gloss white vinyl
- High Bond Gray adhesive
- Solvent, eco-sol, latex and UV Ink Jet Printable

TECHNICAL DATA

Face Material	3.5-mil flexible vinyl
Color and Finish	White high gloss
Adhesive	Permanent acrylic High Bond Gray
Liner	72# polycoated bleached kraft with Ritrama logo

TYPICAL CHARACTERISTICS

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on:)	15 min.	24 hr.
Stainless Steel	60 oz. /inch	80 oz. /inch
Polyethylene	45 oz. /inch	60 oz. /inch
Polypropylene	50 oz. /inch	65 oz. /inch
Gatorplast™	60 oz. /inch	75 oz. /inch
Gatorfoam®	45 oz. /inch	60 oz. /inch
Sintra®	60 oz. /inch	65 oz. /inch
Diebond ®	75 oz. /inch	85 oz. /inch
Acrylic	80 oz. /inch	85 oz. /inch
Glass	70 oz. /inch	85 oz. /inch
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	1 year	
Outdoor Durability	3 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

The above information is based on research believed to be reliable, but does not constitute a warranty.

All material should be tested by the purchaser to determine suitability of the product for their purposes.



800.253.1569 | wensco.com