Signicade® NXT

The Next Generation of the Signicade

- Holds two 24"W x 36"H signs
- Wheels make the sign frame easy to move
 - wheels engage when sign stand is tilted
- Rounded profile
 - pleasantly curved top and sides elevate your message
- Quick-Change[™] feature
 - change signs in seconds, signs easily slide in and out
 - use rigid sign material 3/16" thick or less
- · Concealed hinge doubles as a handle
- No Maintenance
 - all plastic, use indoors and out
- Built-in tether keeps sign faces at perfect angle
- Hidden sand fill ports on back side of sign panel
 - ballast with up to 10 lbs. of dry sand
- Stay Tabs™ensure signs stay securely in place
- Stacking lugs keep stacked units from sliding







WHEELS 1

Signicade® NXT

OUTSIDE DIMENSIONS: 45"H x 30.5"W x 3"D


DIMENSIONS OF RECESSED SIGN AREA: 35"H x 24.13"W

WEIGHT: 17 lbs.

COLORS: White and Black, Custom Colors Available

2 SIGNS PER FRAME

Holds Signs 24"W x 36"H (up to 3/16" thick)



Tamper-free, attached with rivets Collapses when frame is closed

• Holds frame open at 35° angle

Galvanized, braided steel wire

Tether



Sand Ballasting Instructions


Each sign frame has two fill holes, one on each side of the frame.

Remove plug from fill hole and fill each hole with sand. 5 lbs. of sand per hole for a total of 10 lbs. per sign frame is recommended.

Play sand is suggested for ease of filling.

MADE IN THE USA US Patents Pending

Sign Insertion Instructions:



1. Slide sign down through the tabs



2. Slide through, pulling sign in front of bottom slot until sign hits the ground



3. Push sign up into top slot



4. Slide sign down into bottom slot

Slide in a Message Board...



or a Marker Board...



PLASTICADE®

100 Howard Avenue Des Plaines, IL 60018 phone (800) 772-0355 info@plasticade.com Plasticade.com





800.253.1569 wensco.com