

AnPro Stick

The Perfect Solution
For Sign Cabinets.

Specifications

Viewing Angle	180° Optics
Input Voltage	12VDC
Watts	1.5w/mod
Luminous Efficacy	110 (lm/W)
CT	7500K
Model	G2G ANPRO 180
Protection Grade	IP67
Packaging	6PCS/Inner Box, 12PCS/Outer Box
Warranty	7 Year (Product) / 5 Year (Labor)
Operating Temp.	-40°~ +60 °C / -40° ~ +140 °F
Storage Temp.	-40°~ +70 °C / -40° ~ +158 °F
Cascade	25 mods single-ended power feed 50 mods double-ended power feed



110lm/w **IP67**

- Designed for Sign Cabinet
- UV and IR Protected
- L70 rating of 50,000 hours
- 3M double face tape and mechanical mounting options

Recommended Coverage Chart

Depth	SF			DF		
	3"	4"	5"-8"	6"	8"	10"-16"
Spacing	3"	10"	12"	7"	10"	12"

Led Stick Product Options List

LED Sign Module	Dimensions	Voltage	Power	Lm(Per Stick)	Module/Stick	Qty 60W Power Supply	
Anpro Stick 2FT	SF	21.91"	12VDC	4.5W	495	3Mods	13Sticks
	DF			9W	990	6Mods	6 Sticks
Anpro Stick 30IN	SF	27.91"	12VDC	6W	660	4Mods	10Sticks
	DF			12W	1320	8Mods	5 Sticks
Anpro Stick 3FT	SF	33.91"	12VDC	7.5W	825	5Mods	8 Sticks
	DF			15W	1650	10Mods	4 Sticks
Anpro Stick 42IN	SF	39.91"	12VDC	9W	990	6Mods	6 Sticks
	DF			18W	1980	12Mods	3 Sticks
Anpro Stick 4FT	SF	45.91"	12VDC	10.5W	1155	7Mods	5 Sticks
	DF			21W	2310	14Mods	2 Sticks
Anpro Stick 5FT	SF	57.91"	12VDC	13.5W	1485	9Mods	4 Sticks
	DF			27W	2970	18Mods	2 Sticks
Anpro Stick 64IN	SF	61.91"	12VDC	15W	1650	10 Mods	4 Sticks
	DF			30W	3300	20Mods	2 Sticks
Anpro Stick 6FT	SF	69.91"	12VDC	15W	1650	10 Mods	4 Sticks
	DF			30W	3300	20Mods	2 Sticks
Anpro Stick 7FT	SF	81.91"	12VDC	18W	1980	12 Mods	3 Sticks
	DF			36W	3960	24Mods	1 Sticks
Anpro Stick 8FT	SF	93.91"	12VDC	21W	2310	14Mods	2 Sticks
	DF			42W	4620	28Mods	1 Sticks
Anpro Stick 9FT	SF	105.91"	12VDC	24W	2640	16Mods	2 Sticks
	DF			48W	5280	32Mods	1 Sticks
Anpro Stick 117IN	SF	114.91"	12VDC	24W	2640	16Mods	2 Sticks
	DF			48W	5280	32Mods	1 Sticks
Anpro Stick 10FT	SF	117.91"	12VDC	27W	2970	18Mods	2 Sticks
	DF			54W	5940	36Mods	1 Sticks