

7227 Series | Print Media: Intermediate, Gray Adhesive

Series 7227 is a premium, five-year outdoor durable gloss white film with gray adhesive for blackout. Ideal for slightly curved surface applications. Excellent for use in medium-term promotional, point of purchase displays, trade show displays, outdoor signage, and banners.

Film Technology | Calendered (PVC)

Film Thickness | 3.0 mil

Color | 002 Gloss White

Outdoor Durability | 5 Years

Blockout | Yes

Adhesive | Permanent (Gray)

Liner | 90#

Shelf Life | 1 Year

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die Yes Flat Bed Yes Sheetable Yes Laminate Yes	Thermal Transfer No Solvent Yes Eco-Solvent Yes Latex Yes UV Yes Screen Yes	Wet Apply Yes Min. App. Temp. 50°F Interior / Exterior Yes

<p><u>FILM</u></p> <ul style="list-style-type: none"> • Film Thickness (mils/μm) - 3.0 • Film Weight (gsm) - N/A • Gloss - 60° Reflection • Opacity (%) - N/A • Tensile Strength (lbs/in) - N/A • Elongation - N/A • Dimensional Stability - N/A 	<p><u>Adhesive</u></p> <ul style="list-style-type: none"> • Adhesive Type - Permanent Solvent, Pigmented Gray • Adhesive Thickness (mils/μm) - N/A • Adhesive Color - Gray • Peel Strength (lbs/in) - (PSTC-1, 180° peel @ 12"/min., 73°F, Tested on SS = 15 min. 3.5 lbs./inch / 24 hr. 4.7 lbs./inch
<p><u>LINER</u></p> <ul style="list-style-type: none"> • Liner Weight (#/gsm) - 90# • Liner Type - Polycoated Bleached Kraft • Liner Thickness (mils/μm) - N/A • Release Force - N/A 	<p><u>PERFORMANCE GUIDANCE</u></p> <ul style="list-style-type: none"> • Application Temp. - 50°F • Service Temp. - -40°F to +180°F • Shelf Life - 1 Year • Storage Temp. / Rel. Humidity - @ 73°F / 50% • Outdoor Durability - 5 Years

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>