

3400 Series | Lumina Premium Cast Translucent Film with Synthetic Liner

Lumina® by FDC 3400 Series is a 6.0 mil holographic film coated with a permanent acrylic pressure-sensitive adhesive on a 90# layflat liner. The 90# liner provides excellent dimensional stability for digital printing. This film accepts a variety of solvent-based, eco-solvent, latex, and UV curable inks common to wide format digital printing systems.

Film Technology | Holographic

Film Thickness | 6 mil

Color | Silver Holographic

Outdoor Durability | 1 Years

Finish | Gloss

Blockout | Yes

Adhesive | Clear Permanent (Emulsion Acrylic)

Liner | 90#

Conformability | Flat Surfaces, Light Curves

Shelf Life | 1 Year



800.253.1569 | wensco.com

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die Yes Flat Bed Yes Sheetable Yes Laminate Yes / Cold	Thermal Transfer Yes Solvent Yes Eco-Solvent Yes Latex Yes UV Yes Screen Yes	Wet Apply Yes Min. App. Temp. 50°F Interior / Exterior Yes

<p><u>FILM</u></p> <ul style="list-style-type: none"> • Film Thickness__ (mils/μm) 6.0 / 152 (+/- 10%) • Film Weight__ (gsm) 190 • Gloss__ 60° >70 • Opacity__ (%) 99 • Tensile Strength__ N/A • Elongation__ (%) N/A • Dimensional Stability__ MD < 1.00 mm / CD < 1.00 mm 	<p><u>ADHESIVE</u></p> <ul style="list-style-type: none"> • Adhesive Type__ Emulsion Acrylic • Adhesive Thickness__ (mils/μm) 0.8-1.0 / 20-25 • Adhesive Color__ Clear • Peel Strength__ (lbs/in) 24 hrs 3.8 / 17
<p><u>LINER</u></p> <ul style="list-style-type: none"> • Liner Weight__ (#/gsm) 90 / 145 • Liner Type__ White 2-side PE-Coated Kraft • Liner Thickness__ (mils/μm) 6.7 / 170 • Release Force__ @ 360" / min (g/2") 70-100 	<p><u>PERFORMANCE GUIDANCE</u></p> <ul style="list-style-type: none"> • Application Temp.__ > +50 °F • Service Temp.__ -40 °F to 200 °F • Shelf Life__ 1 year • Storage Temp. / Rel. Humidity__ 70°F (21°C) and 50% relative humidity • Outdoor Durability__ 1 year

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>