



Product Data Bulletin v.02/16/2024

7304 Series | Lumina Print Media: Vehicle Marking Grade Reflective

Lumina 7304 series Is a vehicle marking grade reflective vinyl film designed for printing vehicle graphics. It features a repositionable and slidable air egress adhesive system that makes it ideal for vehicle marking applications, including full and partial wrap.

Film Technology | Retro-reflective - PVC

Film Thickness | 5.9 mil

Color | White

Outdoor Durability | 7 years

Finish | Gloss

Blockout | No

Adhesive | Repositionable/Air-Egress

Liner | 90#

Conformability | Simple Curves/Complex curves

Shelf Life | 1 Year

CUTTING	PRINTING	INSTALLATION
Computer Cut Yes	Thermal Transfer No	Wet Apply No
Steel Rule Yes	Solvent Yes	Min. App. Temp. 59°F
Thermal Die Yes	Eco-Solvent Yes	Interior / Exterior Yes
Flat Bed Yes	Latex Yes	
Sheetable Yes	UV Yes	
Laminate Yes / Cold	Screen Yes	



v.02/16/2024



FILM

- Film Thickness_(mils/µm) 5.9 Mil 160 µm
- Film Weight (gsm) N/A
- Gloss 80%
- **Opacity**__ (%) N/A
- Tensile Strength__ 25.5 N/25mm width
- **Elongation**__ (%) 110%
- Dimensional Stability__ N/A

ADHESIVE

- Adhesive Type__ Acrylic
- Adhesive Thickness (mils/µm) .08-1.0 / 20-25
- Adhesive Color Clear
- Peel Strength __ (lbs/in) (N/25mm) 24 hrs. 5.8 / 25

<u>LINER</u>

- Liner Weight__ (#/gsm) 90 / 145
- Liner Type __ White Clay Coated Kraft
- Liner Thickness__ (mils/µm) 6.7 / 170
- **Release Force**__ @ 360" / min (g/2") 15-30

PERFORMANCE GUIDANCE

- **Application Temp.**__ On clean, dry substrate > +59 °F
- Service Temp. -40 °F to 180 °F
- Shelf Life__ up to 1 year
- Storage Temp. / Rel. Humidity__ 70°F (21°C) and 50% relative humidity
- Outdoor Durability__ up to 7 years

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

