# ThermoBANNER<sup>™</sup>2



- Great for awnings, permanent banners, umbrellas, tire covers, & flexible truck side coverings
- Can be applied with a hand iron
- Excellent outdoor durability
- Pressure-sensitive carrier enables easy weeding and repositioning

White

TB2-7100\*

Black TB2-7236\* Red TB2-7301★ Blue TB2-7522\*

Green TB2-7633 \*

## **Acceptable Fabrics**

Heat-sensitive surfaces, coated canvas, most vinyl, and plastic coated surfaces Excluding Nylon

# Sizing Available

Available Widths (in.): 20" only Available Lengths (ft.): 15', 30', and 66' rolls

#### **Thickness**

6.8 mils/170 microns

### **Special Precautions**

\*Cannot be layered. This is a PVC product, which will emit hazardous fumes when cut with a laser machine!



45° Blade Recommended



Cut this material in mirror image



212°F - 285°F



Very little pressure required. Use hand iron or standard heat press.



10-15 Seconds



**Peel Cold** 



Wash warm, tumble dry normal. Suitable for dry-cleaning.



# SpecialtyMaterials.com | 877.437.8556



Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics. All technical information and recommendations are based on tests we believe to be reliable. However, we cannot guarantee performance for conditions not under manufacturer's control. Before using, please determine the suitability of product for its intended use. The user assumes all risk and liability, whatsoever, in connection with the use of this product. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective by manufacturer.